


CS420 (Deterministic) Finite Automata

Thursday, September 8, 2022

UMass Boston Computer Science



Announcements

• **Quizzes**

- Quiz 1 returned
- Use gradescope issue ticket for questions / complaints

• **HW**

- Weekly; in/out Sunday midnight
- HW 0 due Sunday 9/11 11:59pm EST
- ~4-5 questions, Paper-and-pencil proofs (no programming)
- Discussing with classmates ok; Final answers written up / submitted individually

• **Lectures**

- Not recorded but closely follow the listed textbook chapters

• **Office Hours**

- Thurs 12:30-2pm (in person)
- Fri 4-5:30pm (zoom, access link from blackboard)
- Let me know if advance if possible, but drop-ins also fine

Last Time: The Theory of Computation ...

Formally defines mathematical models of computation



In order to:



1. Make predictions (about computer programs)

- If possible

```
function( x, y, z, n) {  
  if n > 2 && x^n + y^n == z^n {  
    printf("hello, world!\n");  
  }  
}
```

Fermat's Last Theorem
(unknown for ~350 years,
solved in 1990s)

2. Compare the models to each other

- Java vs Python? The same?

3. Explore the limits of computation


- What programs cannot be written?

Last Time: Computation = Programs!

```
Lesson 1 - CFG Grammar
E -> T E'
E' -> + T E'
E' ->
T -> F T'
T' -> * F T'
T' ->
F -> ( E )
F -> int

Lesson 2 - FA Lexer
NFA machine contains 11 total states


Lesson 3 - Runtime Parser
Reading expression "3+5*7"
NonTerminal E: , Line 1, Column 1
NonTerminal T: Line 1, Column 1
```



```
1 import RPi.GPIO as GPIO
2 import time
3 import numpy as np
4 import cv2
5 from datetime import datetime
6 import os
7 import smtplib
8 from email.MIMEBase import MIMEBase
9 from email.MIMEText import MIMEText
10 from email import Encoders
11 gmail_user = "FROM MAIL ID@gmail.com" #Sender email address
12 gmail_pwd = "FROM MAIL PASSWORD" #Sender email password
13 to = "TO MAIL ID@gmail.com" #Receiver email address
14 subject = "Security Alert"
15 text = "There is some activity in your home. See the attached picture"
16
17 sensor = 4
18
19 GPIO.setmode(GPIO.BCM)
20 GPIO.setup(sensor, GPIO.IN, GPIO.PUD_DOWN)
21
```



```
case CurrentState is
when idle =>
if (d_en = 1) then
NextState <- wait; StartCnt <- 1;
else NextState <- idle;
end if;
when wait =>
if (cnt = n) then
NextState <- ready; end <- 1;
else NextState <- wait;
end if;
when ready =>
NextState <- idle;
(...);
end case;
```



More powerful
More complex
Less restricted



Intuition for this course:

- A **model of computation** defines a **class of machines** (each box)
- Think of: a **class of machines** = a **“Programming Language”!**
- Think of: a **single machine instance** = a **“Program”!**

Last Time: Computation = Programs!

Very important Note: I use this “programs” and “programming language” analogy to help you understand CS420 topics, by comparing them to ideas you’ve seen before

```
GPIO
P
ort datetime

Itipart import MIMEMultipart
se import MIMEBase
xt import MIMEText
Encoders
M MAIL_ID@gmail.com" #Sender email address
MAIL_PASSWORD" #Sender email password
gmail.com" #Receiver email address
ty Alert"
some activity in your home. See the attached pict


.BCH)
GPIO.setup(sensor, GPIO.IN, GPIO.PUD_DOWN)
```



Linear Bounded Automata

But don't get confused: “programs” and “programming languages” are not formal terms defined in this course.

More powerful
More complex
Less restricted



```
Lesson 1
E -> T E'
E' -> + T E'
E' ->
T -> F T'
T' -> * F T'
T' ->
F -> ( E )
F -> int

Lesson 2 - FA Lexer
NFA machine contains 11 total states

Lesson 3 - Runtime Parser
Reading expression "3+5*7"
NonTerminal E: , Line 1, Column 1
NonTerminal T: Line 1, Column 1
```

Finite State

```
if (cnt = n) then
  NextState ← ready; end ← 1;
else NextState ← wait;
end if;
```




Intuition for this course:

- A model of computation
- Think of: a class of machines = a “Programming Language”!
- Think of: a single machine instance = a “Program”!

In fact, the term **language** will formally mean something else (later)

Last Time: Models of Computation Hierarchy




Finite Automata: “Simple” Computation / “Programs”



Finite Automata

- A **finite automata** or **finite state machine (FSM)** ...
- ... computes with a finite number of states

A Microwave Finite Automata



Finite Automata: Not Just for Microwaves

Finite Automata:
a common
programming pattern



State pattern

From Wikipedia, the free encyclopedia


The **state pattern** is a [behavioral software design pattern](#) that allows an object to alter its behavior when its internal state changes. This pattern is close to the concept of [finite-state machines](#). The state pattern can be interpreted as a [strategy pattern](#), which is able to switch a strategy through invocations of methods defined in the pattern's interface.

Computation Simulating Other Computation
(a common theme this semester)


Video Games Love Finite Automata

The basic idea is that a character is engaged in some particular kind of action at any given time. The actions available will depend on the type of gameplay but typical actions include things like idling, walking, running, jumping, etc. These actions are referred to as **states**, in the sense that the character is in a “state” where it is walking, idling or whatever. In general, the character will have restrictions on the next state it can go to rather than being able to switch immediately from any state to any other. For example, a running jump can only be taken when the character is already running and not when it is at a standstill, so it should never switch straight from the idle state to the running jump state. The options for the next state that a character can enter from its current state are referred to as **state transitions**. Taken together, the set of states, the set of transitions and the variable to remember the current state form a **state machine**.

The states and transitions of a state machine can be represented using a graph diagram, where the nodes represent the states and the arcs (arrows between nodes) represent the transitions. You can think of the current state as being a marker or highlight that is placed on one of the nodes and can then only jump to another node along one of the arrows.



Finite Automata in Video Games



ValveSoftware / halflife

<> Code 1.6k Issues Pull requests 23 Actions Projects Wiki

5d761709a3 halflife / game_shared / bot / simple_state_machine.h


Alfred Reynolds initial seed of Half-Life 1 SDK

0 contributors

85 lines (67 sloc) | 2.15 KB

```
1 // simple_state_machine.h
2 // Simple finite state machine encapsulation
3 // Author: Michael S. Booth (mike@turtlerockstudios.com), November 2003
4
5 #ifndef _SIMPLE_STATE_MACHINE_H_
6 #define _SIMPLE_STATE_MACHINE_H_
7
8 //-----
9 /**
10  * Encapsulation of a finite-state-machine state
11  */
12 template < typename T >
13 class SimpleState
```


Model-view-controller (MVC) is an FSM



A Finite Automata = a “Program”

- A very limited “program” that uses finite memory
 - Actually, only 1 “cell” of memory!
 - States = the possible things that can be written to memory
- Finite Automata has different representations:
 - Code (wont use in this class)
 - State diagrams

Finite Automata state diagram



A Finite Automata = a “Program”

- A very limited program with finite memory
 - Actually, only 1 “cell” of memory!
 - States = the possible things that can be written to memory
- Finite Automata has different representations:
 - Code
 - State diagrams
 - Formal mathematical description

Finite Automata: The Formal Definition

DEFINITION

5 components

A *finite automaton* is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

1. Q is a finite set called the *states*,
2. Σ is a finite set called the *alphabet*,
3. $\delta: Q \times \Sigma \rightarrow Q$ is the *transition function*,
4. $q_0 \in Q$ is the *start state*, and
5. $F \subseteq Q$ is the *set of accept states*.

Sets and Sequences

- Both are: mathematical objects that group other objects
- **Members** of the group are called **elements**
- Can be: **empty, finite, or infinite**
- Can contain: **other sets or sequences**

Sets

- **Unordered**
- Duplicates **not** allowed
- Common notation: { }
- “Empty set” denoted: \emptyset or { }
- A **language** is a (possibly infinite) set of strings

Sequences

- **Ordered**
- Duplicates ok
- Common notation: (), or **just commas**
- “Empty sequence”: ()
- A **tuple** is a finite sequence
- A **string** is a finite sequence of characters

Set or Sequence ?

A **function** is ...

... a **set of pairs**
(1st of each pair from **domain**, 2nd from **range**)

... can write it in many ways: as a mapping, a table, ...

DEFINITION

A *finite automaton* is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

sequence

set

1. Q is a finite set called the *states*,

Set of pairs (domain)

2. Σ is a finite set called the *alphabet*,

set

3. $\delta: Q \times \Sigma \rightarrow Q$ is the *transition function*,

4. $q_0 \in Q$ is the *start state*, and **Set (range)**

Don't know!
(states can be anything)

5. $F \subseteq Q$ is the *set of accept states*.

set

A **pair** is ... a **sequence** of 2 elements

Finite Automata: The Formal Definition

DEFINITION

5 components


A *finite automaton* is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

1. Q is a finite set called the *states*,
2. Σ is a finite set called the *alphabet*,
3. $\delta: Q \times \Sigma \rightarrow Q$ is the *transition function*,
4. $q_0 \in Q$ is the *start state*, and
5. $F \subseteq Q$ is the *set of accept states*.

DEFINITION

A *finite automaton* is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

1. Q is a finite set called the *states*,
2. Σ is a finite set called the *alphabet*,
3. $\delta: Q \times \Sigma \rightarrow Q$ is the *transition function*,
4. $q_0 \in Q$ is the *start state*, and
5. $F \subseteq Q$ is the *set of accept states*.



Example: as state diagram

DEFINITION

A *finite automaton* is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

1. Q is a finite set called the *states*,
2. Σ is a finite set called the *alphabet*,
3. $\delta: Q \times \Sigma \rightarrow Q$ is the *transition function*,
4. $q_0 \in Q$ is the *start state*, and
5. $F \subseteq Q$ is the *set of accept states*.


Note:
Not the same Q

Example: as formal description

$M_1 = (Q, \Sigma, \delta, q_1, F)$, where

1. $Q = \{q_1, q_2, q_3\}$,
2. $\Sigma = \{0, 1\}$,
3. δ is described as

braces =
set notation
(no duplicates)



Example: as state diagram


	0	1
q_1	q_1	q_2
q_2	q_3	q_2
q_3	q_2	q_2

4. q_1 is the start state, and
5. $F = \{q_2\}$.

DEFINITION

A *finite automaton* is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

1. Q is a finite set called the *states*,
2. Σ is a finite set called the *alphabet*,
3. $\delta: Q \times \Sigma \rightarrow Q$ is the *transition function*,
4. $q_0 \in Q$ is the *start state*, and
5. $F \subseteq Q$ is the *set of accept states*.



Example: as state diagram

Example: as formal description

$M_1 = (Q, \Sigma, \delta, q_1, F)$, where

1. $Q = \{q_1, q_2, q_3\}$,
2. $\Sigma = \{0, 1\}$, ← Possible inputs
3. δ is described as


	0	1
q_1	q_1	q_2
q_2	q_3	q_2
q_3	q_2	q_2

4. q_1 is the start state, and
5. $F = \{q_2\}$.

DEFINITION

A *finite automaton* is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

1. Q is a finite set called the *states*,
2. Σ is a finite set called the *alphabet*,
3. $\delta: Q \times \Sigma \rightarrow Q$ is the *transition function*,
4. $q_0 \in Q$ is the *start state*, and
5. $F \subseteq Q$ is the *set of accept states*.



Example: as state diagram

Example: as formal description

$M_1 = (Q, \Sigma, \delta, q_1, F)$, where

1. $Q = \{q_1, q_2, q_3\}$,
2. $\Sigma = \{0, 1\}$,

3. δ is described as

	0	1
q_1	q_1	q_2
q_2	q_3	q_2
q_3	q_2	q_2


Annotations: "And this is next input symbol" points to the input symbols 0 and 1. "If in this state" points to the rows q_1 , q_2 , and q_3 . "Then go to this state" points to the resulting states in the table.

4. q_1 is the start state, and
5. $F = \{q_2\}$.

DEFINITION

A *finite automaton* is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

1. Q is a finite set called the *states*,
2. Σ is a finite set called the *alphabet*,
3. $\delta: Q \times \Sigma \rightarrow Q$ is the *transition function*,
4. $q_0 \in Q$ is the *start state*, and
5. $F \subseteq Q$ is the *set of accept states*.



Example: as state diagram

Example: as formal description

$M_1 = (Q, \Sigma, \delta, q_1, F)$, where

1. $Q = \{q_1, q_2, q_3\}$,
2. $\Sigma = \{0, 1\}$,
3. δ is described as


	0	1
q_1	q_1	q_2
q_2	q_3	q_2
q_3	q_2	q_2

4. q_1 is the start state, and
5. $F = \{q_2\}$.

DEFINITION

A *finite automaton* is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

1. Q is a finite set called the *states*,
2. Σ is a finite set called the *alphabet*,
3. $\delta: Q \times \Sigma \rightarrow Q$ is the *transition function*,
4. $q_0 \in Q$ is the *start state*, and
5. $F \subseteq Q$ is the *set of accept states*.



Example: as state diagram

Example: as formal description

$M_1 = (Q, \Sigma, \delta, q_1, F)$, where

1. $Q = \{q_1, q_2, q_3\}$,
2. $\Sigma = \{0, 1\}$,
3. δ is described as

	0	1
q_1	q_1	q_2
q_2	q_3	q_2
q_3	q_2	q_2

4. q_1 is the start state, and

5. $F = \{q_2\}$.

DEFINITION

A *finite automaton* is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

1. Q is a finite set called the *states*,
2. Σ is a finite set called the *alphabet*,
3. $\delta: Q \times \Sigma \rightarrow Q$ is the *transition function*,
4. $q_0 \in Q$ is the *start state*, and
5. $F \subseteq Q$ is the *set of accept states*.

A “Programming Language”

Remember: this is just way to help your intuition

But these are not formal terms.
Don't get confused

Programming Analogy

Example: as formal description

$M_1 = (Q, \Sigma, \delta, q_1, F)$, where

1. $Q = \{q_1, q_2, q_3\}$,
2. $\Sigma = \{0, 1\}$,
3. δ is described as

	0	1
q_1	q_1	q_2
q_2	q_3	q_2
q_3	q_2	q_2 ,

4. q_1 is the start state, and
5. $F = \{q_2\}$.


In-class Exercise

Come up with a formal description of the following machine:

DEFINITION

A *finite automaton* is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where


1. Q is a finite set called the *states*,
2. Σ is a finite set called the *alphabet*,
3. $\delta: Q \times \Sigma \rightarrow Q$ is the *transition function*,
4. $q_0 \in Q$ is the *start state*, and
5. $F \subseteq Q$ is the *set of accept states*.



In-class Exercise: solution

- $Q = \{q1, q2, q3\}$
- $\Sigma = \{a, b\}$
- δ
 - $\delta(q1, a) = q2$
 - $\delta(q1, b) = q1$
 - $\delta(q2, a) = q3$
 - $\delta(q2, b) = q3$
 - $\delta(q3, a) = q2$
 - $\delta(q3, b) = q1$
- $q_0 = q1$
- $F = \{q2\}$

$$M = (Q, \Sigma, \delta, q_0, F)$$



A Computation Model is ... (from lecture 1)

- Some base definitions and axioms ...


DEFINITION

A *finite automaton* is a 5-tuple $(Q, \Sigma, \delta, q_0, F)$, where

1. Q is a finite set called the *states*,
2. Σ is a finite set called the *alphabet*,
3. $\delta: Q \times \Sigma \rightarrow Q$ is the *transition function*,
4. $q_0 \in Q$ is the *start state*, and
5. $F \subseteq Q$ is the *set of accept states*.

- And rules that use the definitions ...

Computation with FSMs (JFLAP demo)



• **Input: “1101”**

FSM Computation Model

Informally

- Program = a finite automata
- Input = string of chars, e.g. "1101"

To run a program:

- Start in "start state"
- Repeat:
 - Read 1 char;
 - Change state according to the transition table
- Result =
 - "Accept" if last state is "Accept" state
 - "Reject" otherwise

Formally (i.e., mathematically)

- $M = (Q, \Sigma, \delta, q_0, F)$
- $w = w_1 w_2 \cdots w_n$
- $r_0 = q_0$
- $\delta(r_i, w_{i+1}) = r_{i+1}$, for $i = 0, \dots, n - 1$

Let's come up with **nicer notation** to represent this part

- M *accepts* w if
sequence of states r_0, r_1, \dots, r_n in Q exists ...
with $r_n \in F$

Still a little verbose

Check-in Quiz 9/8

On gradescop